□□□□ □□□□ □□□□□ □□□□ □□□□□□□□□ □□□□□ □□□□□ □□ □□□□ 2205 □□□□□□ □□□ □□□□□ □□□□□□ □□□ □□□□□ □□□□□□ □□□□ .

□□□□□ □□□□□□□□□ □□□□□ □□□□□□ □□□ □□□□□ □□ □□□□□□□□-

- □□□ □□□□□ SCM
- 2205 □□□□□□ :□□□□□□
- □□□ □□ □□□□□ :□□□□□□□
- □□ 13.52 □□ 12 □□ 10 □□ 8 :□□□□□□ □□□
- 285 □□□□□□ □□□□□□mm
- □□□□□□ □□□□ □□
- □□□□ □□□□□ □□ □□□□□□
- 1200 □□□ □□ □□□□□□ □□□□ 1 □□□□ □□□□ 2 □□□□□□ □□□□□MM

□□ □□□ SCM □□□□□ □□□□□□ □□□□ □□□□□□□□ □□□□□ □□□□□ □□-

KEBIL科比奥®

KEBIL科比奥®

□□□□□ □□□□□□ □□□□ □□□□ □□□□□□□□ □□□□□ □□□□ □□□□□□ □□□□□ □□□□□ □□ □□□□□ -


Project name
50
M10
45
205
50±0.2
17±0.2
110
285
40
29
Shenzhen Launch Co., Ltd
50
50
深圳市朗驰商贸有限公司
SHENZHEN LAUNCH CO., LTD.
表面处理
材 料
设 计
裴佳辉
图号:SCM
校 对
名称:Spigot
工 艺
审 核
批 准
数 量
共 页
第 页
版 次
V001

[redacted] -

SCM/RCM:305x290x130MM
2014/03/19

□□□□□ □□□□□□ □□□□ □□□□ □□□□ □□□□□□ □□□ □□□□ □□□□□□□□ □□□□□ □□ □□□□□□□ □□□ -

KEBIL科比奥®

KEBIL科比奥®

KEBIL科比奥

KEBIL科比奥

□□□□□□□□ □□□□ □□□□□□ □□□□ □□□□□ □□□ -

□□□ □□□□□ □□□□□□ □ [□□□□□□□□ □□□□□□□]

Spring loaded hinges

Stainless steel spring loaded hinges

-Made of SS 316

- For use of 8-12.76mm glass

Maximum door leaf weight : 30 kg /pair

Maximum door leaf width : 900mm

Spring can be adjusted for closing speed control .

Part # G-G

Part # G-R

Part # G-W

□□□□□□□□□□□ □□□□□□ □□□□□ □□□□□□□ □ □□□□□□ □□□□□ -

Magnetic glass latches

Stainless steel glass latches

-Made of SS 316

- For use of 8-12.76mm glass

- types :

• glass to glass latch 180 degree

• glass to glass latch 90 degree (in swing & out swing)

• glass to wall latch

• glass to round post latch

Maximum door leaf weight : 30 kg /pair

Maximum door leaf width : 900mm

Spring loaded hinges

Glass latches with plastic cover

MODEL # GL-180

MODEL # GL-90

MODEL # GL-W

MODEL # GL-R

Spring loaded hinges

Glass latches with stainless steel cover

Gl-180SS

Gl-90SS

GL-WSS

GL-PSS