rubinetto in vetro tondo di acciaio inossidabile verniciato nero, per recinzioni per piscine senza telaio, disponibili anche altri colori.

Descrizione del prodotto

Prodotto Mame	rubinetto tondo in acciaio inox con vernice nera
Materiale	Acciaio inossidabile 316 / duplex 2205
finire	Lucidato a specchio / satinato
Per Glass Thickness	8-13.52mm
Altezza	168 millimetri
dimensione della base del rubinetto	100x100mm
Peso netto	1.08kg / piece
Metodo di fabbricazione	Casting (alta qualità)
dettagli sul confezionamento	1) Un pezzo in una borsa a bolle, quindi in una scatola bianca 2) 12 pezzi in cartone di cartone 365x330x230mm 3) Imballaggio come requisiti dei clienti
Applicazione	Recinzione della piscina, inferriata di vetro del balcone, ponte senza cornice ringhiera di vetro, scale
Certificatione	sì. Meet Australia e Nuova Zelanda norme
Sampio	A disposizione
MOQ	1 pc
OEM e & ODM Servizio	A disposizione

rubinetto tondo in acciaio inox con vernice nera Destails

1) Disegno tecnico di spigot di vetro

2) rubinetto in vetro tondo di acciaio inossidabile verniciato nero



Altri colori di paiting disponibili







3) Guida all'installazione per rubinetto in vetro duplex 2205 in acciaio inossidabile



fixing method: base plate spigots


Mark out the centre line of proposed glass fence with a chalk line. Determine clamp location based on a sheet size (recommendation on pages 1 & 2). Use base plate as a template to mark out the hole positions and drill holes to suit.

Note: Do not exceed 100mm gaps between glass panels. Optimum gap is 40mm to 60mm

Now the base plated spigots can be fitted to the floor and plumbed via shims (not supplied) under the base plates. Be sure to tighten firmly as the smallest of movement at the base plate will result in noticeable movement at the bottom of the glass fearer.


Tip: By setting the two outer spigots of your total span, a string line can be run in the 'throat' of the spigots, giving correct height for all spigots in between

Note: Do not exceed 100mm gap from the fixing surface to the bottom of the glass



When all spigots are installed, slip domical cover the top of the spigot to hide fixings. It will be necessary to turn the adjustment screws on the spigot face all the way in to allow cover to pass over

Note: Same installation method applies to round base plate spigot




The glass is then installed to the spigots.

Place plastic packers between glass & spigot, at no stage should glass touch the metal

How adjustability works:

- 1. Place glass in spigot
- 2. Fix/ tension glass both sides with allen key



Imballaggio di sicurezza per bicchierino in vetro duplex 2205 in acciaio inossidabile

1. Un pezzo in una borsa a bolle, quindi in una scatola bianca. 12 pezzi in cartone di cartone 365x330x230mm.

2. Imballaggio come requestiments dei clienti.



Progetti duplex di vetro duplex 2205 in acciaio inox







FAQ

1. che materiale hai?

SS304, SS316, SS316L, duplex 2205, ecc.

2. potete inviarmi il vostro intero listino prezzi?

Siamo spiacenti, poiché il prezzo si riferisce a molti fattori, quali quantità, tipo di materiale, trattamento superficiale e così via, ti offriremo un preventivo esatto dopo aver confermato i tuoi requisiti dettagliati.

3. Offrite OEM & Servizio ODM?

Sì, possiamo fabbricare i prodotti secondo i vostri disegni tecnici o campioni. Siamo professionisti nella microfusione, pressofusione, stampaggio, lavorazione CNC, ecc.

4. Che tipo di pagamento accetti?

T / T, L / C, PayPal, West Union, ecc.

5. qual è il tuo termine di pagamento?

T / T (30/70) o L / C a vista.

6. Qual è il tuo tempo di consegna?

Entro 5 giorni lavorativi per articoli hot-sale. 15-25 giorni lavorativi per gli ordini da bagno.

7. offrite il servizio post-vendita?

Naturalmente, qualsiasi domanda dopo aver acquistato i nostri prodotti, ti risponderemo entro 24 ore.

Informazioni aziendali

Shenzhen Launch Co., Ltd was established in 2004, located at Nanshan District, Shenzhen, and one hour by car from Hongkong International Airport. Our main product is high-grade building materials includes stainless steel balustrade post, staircase handrail, balcony guardrail, swimming pool fence and other high-grade building materials. All the products are designed strictly according to the high-end market requirements. We have our own factory in Tangxia Town, Dongguan, has a variety of precision equipment more than 50 sets: CNC lathe, milling machine, punching machine, pipe cutter, argon welder, drilling machine, polisher, etc. which can provide customers with complete product processing services. With the German SPECTRO Spectrometer, we insist on testing every batch of materials to ensure that the material is highly qualified. We also have hardness gauge, secondary element and other test equipment to ensure the products meets customers' requirements.







Please do not hesitate to contact us if you have any requirement regarding our production lines, you can expect a timely reply with professional solutions!



Own factory, shortest lead time.



Can help customers design product drawings based on customer ideas and design engineering installation drawing according to the customer site sketch.



Sample order, trial order acceptable.



Provide material test report to ensure that the material is qualified.



13 years of industry experience, we can help customers recommend the best solution to help customers save cost.



More than 13 years experience in hardware industry design and processing, we can provide customized services from design to the sample and small batch trial production.













With premium quality, competitive price and superior service, we won a lot of customers' favor.

Our products are popular in North America, European and Australia.









PRODUCTION PROCESS







CNC lathe



CNC Milling



Stamping



Drilling & Tapping



Polishing

















PACKAGING & DELIVERY





















CONTACT US

WELCOME TO CONTACT US. WE WILL DO OUR BEST TO HELP YOU!



CELIA CHEN

Email: sales01@launch-china.cn

S Skype: launch-01



Mob. 86-13590273543

