

Il maggior parte popolare serie di cerniere idrauliche per porte in vetro a chiusura automatica in acciaio inox applicate per porte doccia in vetro. Non è solo di alta qualità (resistente alla ruggine), ma lo mantiene anche silenzioso mentre si chiude la porta.

Caratteristiche della cerniera idraulica della porta di vetro -

- Tipo: vetro a 90 gradi a parete
- Max. larghezza della porta -1 000mm
- Max. peso della porta: 60 kg
- Acciaio inossidabile 304 o 316
- finitura satinata / specchio / nera
- si ferma a 90 gradi, si chiude automaticamente e velocità regolabile

KEBIL 科比奥®





Cerniera per porta in vetro a 90 gradi e 180 gradi con materiale in acciaio inossidabile -



Cerniera per porta in vetro a 90 gradi (materiale in acciaio inossidabile e materiale in alluminio) -



Come installare la cerniera della porta in vetro?

HINGE PARTS



STEP 1 - LINE UP THE MAIN BODY OF THE HINGE ALONG THE DESIGNATED SLOT OF THE ACRYLIC DOOR



NOTE: REFER TO THE PICTURE BELOW AFTER THE DOOR IS INSTALLED.
THE ADJUSTMENT TO THE CLOSING SPEED WILL ALREADY BE SET, NO NEED TO ADJUST

MAIN BODY CONFIGURATION



TOP HALF CONFIGURATION



STEP 2 - SANDWICH THE ACRYLIC WITH THE TOP HALF OF THE HINGE, ALIGNING WITH THE MAIN BODY



MAKE SURE THE SCREW HEADS FACE INSIDE THE ROOM WHEN ATTACHING THE DOOR.

STEP 3 - INSERT THE BOLTS AND TIGHTEN WITH A 4mm HEX KEY



Foto di Pakaging della cerniera della porta di vetro-



