

Specyfikacja	
Nazwa produktu	Aluminiowe przesuwane drzwi BIFOLD DREAD DOUT TERMAL BLASS DOUBLEDNE SZEKOWANE DREOK
Tworzywo	Stop aluminium 6063-T5 Profil szkło akcesoria
Opcje profilu	Marka profilu: chińska marka
	Grubość profilu: 2,0 mm
	Obróbka powierzchniowa: powłoka proszkowa, anodowanie, powłoka PVDF itp.
Opcje szkła	Kolor: biały, czarny, szary, niestandardowy kolor
	Standardowa specyfikacja: 5 mm27a5 mm
	Materiał: szkło hartowane
	Kolor: Ultra Clear, Clear, Frosted, Grey, zielony, niestandardowy kolor
Inne akcesoria	Rodzaje: pojedyncze szkło, lamimowane szkło itp.
	Pasek uszczelniający: EPDM Materail
	Zamka: chińska najlepsza marka
	Track: szyna ze stali nierdzewnej
	Walek: poliamid o wysokiej wytrzymałości





D-shape Handle

The Folding Process is easy to operate



Heavy-Duty Hinge

Single Weight **150kg**



Top Wheel

Prevent The Door From Swinging From Side To Side




Return Pulley


Easy Folding Push Smooth Without Resistance

Configuration


Doors



Sliding



Sliding Stacker




Corner Sliding



Hinged



Bi-fold



Sliding Wardrobe



Showerscreens



Screens



Pivot Door
Entry Units

Windows




Awning




Casement



Louvre



Sliding




Window Wall




Bay



Fixed



Double Hung



Bi-fold




Screens

Glass Types

Variety Of Glass & Profile Available



Temperde glass




Single glass



Double glass



Triple glass



Laminated glass



Frosted glass



Low-E glass



Reflective glass



LIVING ROOM



BALCONY



KITCHEN



BEDROOM

Workshop



1.3D&CAD drawing



2.Thermal break



3.Cutting profile



4.Lock milling



5.Profile assembling



6.Glass assenbling



7.Sealing



8.Testing



9.quarantine